



AT-15SUB-II

High Power Subwoofer System

The AT-15SUB-II extends the usable range of the AT-2015 Pro-Sound Loundspeaker to 38Hz.

Providing high performance and high power output(135dB Peak) in an extremely compact.

Light weight package. One AT-15SUB-II is typically used with 2 AT-2015 Loundspeaker.

Additional units may be used for an enhanced effect.

The AT-2015 Loundspeaker and AT-15SUB-II Subwoofer are designed to work with advanced electronic processors. Guaranteeing consistent performance and reliability of the highest standard.



Component	LF: 1 x 15"
Nominal Impedance	8 Ohms
Sensitivity	105dB SPL Nominal (1W @ 1m [b])
Frequency Response	38Hz ~ 500Hz
Nominal Peak SPL @ 1m [b]	135dB (1W @ 1m [b])
Power Handling	500W (program) 800W (peak)
Recommended Amplifiers	300 To 700W into 4 Ohms
Front Finish	Perforated steel grills
Flying Points	10 Threaded flying points on side and back
Construction	Baltic Birch Ply G textured, polyurethane black coating.
Connectors	2 x NL4MP Speak on 4 pole
Fittings. Handles	4. integral to cabinet.
Dimension : (WxHxD)	470mm x 550mm x 645mm
Weight	37Kg

ASTER PRO-AUDIO INC.

36 ERNEST AVENUE TORONTO ON M2J 3T5
<http://www.aster-proaudio.com>
sales@aster-proaudio.com