

# AT-2015

## 2 Way High Power Pro-sound Speaker



Rotatable asymmetrical horn and unique cabinet architecture ensure versatility.

Switchable passive or active design for precise performance matching to user requirements.



Sophisticated control electronics ensure reliable. Linear operation. Supported with a full range of mounting and flying accessories.

The AT-2015 with 15" woofer and a 1.75" tweeter driver. Flyable, Trapezoidal, Warm, Transparent and clear sound reproduction.

Ideal for Discotheques, Musical halls, Conference halls, and other venues.

| Component                 | 15" Horn / 1.75" Driver                                  |
|---------------------------|----------------------------------------------------------|
| Nominal Impedance         | 8 Ohms                                                   |
| Sensitivity               | 115dB SPL Nominal ( 1W @ 1m [b] )                        |
| Frequency Response        | 35Hz ~ 20KHz $\pm$ 2.5dB                                 |
| Nominal Peak SPL @ 1m [b] | 138dB                                                    |
| Power Handling            | 700W ( program ) 1200W (peak)                            |
| Dispersion                | 80° Horizontal $\times$ 80° Vertical                     |
| Recommended Amplifiers    | 400 To 1000W into 4 Ohms                                 |
| Front Finish              | Perforated steel grills                                  |
| Flying Points             | 3 steel anchor points for flying tracks on side and back |
| Construction              | Baltic Birch Ply G textured. polyurethane back coating.  |
| Connectors                | 2 $\times$ NL4MP Speak on 4 pole                         |
| Fittings. Handles         | 2. integral to cabinet.                                  |
| Dimension : ( WxHxD )     | 428mm $\times$ 694mm $\times$ 400mm                      |
| Weight                    | 27Kg                                                     |